


Adaptadores Hidráulicos - Rosca NPTF

Serie 5502 - Codo 90° Macho NPTF x Hembra NPTF

Rosca Macho NPTF	Rosca Hembra NPTF	Acero al Carbón Zincado # de Parte	PSI
1/8"-27	1/4"-18	5502-2-4	5000
1/8"-27	1/8"-27	5502-2	5000
1/4"-18	1/8"-27	5502-4-2	5000
1/4"-18	3/8"-18	5502-4-6	4000
1/4"-18	1/2"-14	5502-4-8	3000
1/4"-18	1/4"-18	5502-4	5000
3/8"-18	1/8"-27	5502-6-2	4000
3/8"-18	1/4"-18	5502-6-4	4000
3/8"-18	1/2"-14	5502-6-8	3000
3/8"-18	3/8"-18	5502-6	4000
1/2"-14	3/8"-18	5502-8-6	3000
1/2"-14	3/4"-14	5502-8-12	2500
1/2"-14	1/2"-14	5502-8	3000
3/4"-14	1/2"-14	5502-12-8	2500
3/4"-14	1"- 11 1/2	5502-12-16	2000
3/4"-14	3/4"-14	5502-12	2500
1"- 11 1/2	3/4"-14	5502-16-12	2000
1"- 11 1/2	1 1/4" - 11 1/2	5502-16-20	1150
1"- 11 1/2	1"- 11 1/2	5502-16	2000
1 1/4" - 11 1/2	1"- 11 1/2	5502-20-16	1150
1 1/4" - 11 1/2	1 1/4" - 11 1/2	5502-20	1150
1 1/2" - 11 1/2	1 1/2" - 11 1/2	5502-24	1000
2"-11 1/2	2"-11 1/2	5502-32	1000
1/8"-27	1/8"-27	5502C-2	5000
1/4"-18	1/4"-18	5502C-4	5000
3/8"-18	3/8"-18	5502C-6	4000
1/2"-14	1/2"-14	5502C-8	3000
3/4"-14	3/4"-14	5502C-12	2250
1/4"-18	1/4"-18	5502SW-4-4	5000
3/8"-18	3/8"-18	5502SW-6-6	4000
1/2"-14	1/2"-14	5502SW-8-8	3000
3/4"-14	3/4"-14	5502SW-12-12	2250



(1) Macho NPTF
(2) Hembra NPTF
+ C=Compacto

* SW = Un extremo giratorio
SAE 140239

