

General Service Air & Water Hose Non-Oil Resistant

Series 7092 (Red) / 7093 (Black) GST® II Hose



Tube:	Black EPDM
Reinforcement:	Multiple textile plies
Cover:	Red (7092) or Black (7093) EPDM; smooth finish
Temp Range:	-40°F to +212°F (-40°C to +100°C)
Brand Method:	White ink
Brand Example:	PARKER SERIES 7092 GST® II 1/4 ID (6.4 MM) 200 PSI MAX WP MADE IN USA (DATE CODE)
Design Factor:	4:1
Industry Standards:	None applicable
Applications:	• Air, air tools, light chemicals, water • General industrial

Series 7092 / 7093 is economical and versatile for general air, light chemicals, water and applications such as air tool lines lubricated by a light oil mist, but it is NOT suitable for the conveyance or transfer of petroleum products. The EPDM cover resists heat, ozone and weathering.

WARNING!

Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose.

Part Number (Red)	Part Number (Black)	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/100 ft)	Min Bend Rad (in)	Max Rec WP (psi)	Std Pack Qty (ft)
7092-19200	7093-19200	3/16	4.8	2	0.437	11.1	6	2.0	200	800
7092-19300	7093-19300	3/16	4.8	4	0.437	11.1	8	2.0	300	800
7092-25200	7093-25200	1/4	6.4	2	0.500	12.7	9	2.5	200	800
7092-25300	7093-25300	1/4	6.4	4	0.550	14.0	12	3.3	300	800
7092-31200	7093-31200	5/16	7.9	2	0.594	15.1	12	3.3	200	750
7092-31300	7093-31300	5/16	7.9	4	0.625	15.9	14	3.5	300	750
7092-38200	7093-38200	3/8	9.5	2	0.656	16.7	14	3.5	200	700
7092-38300	7093-38300	3/8	9.5	4	0.688	17.5	16	4.0	300	700
7092-50200	7093-50200	1/2	12.7	2	0.813	20.7	20	4.5	200	550
7092-50250	7093-50250	1/2	12.7	2	0.844	21.4	22	4.5	250	550
7092-50304	7093-50304	1/2	12.7	4	0.875	22.2	25	5.0	300	500
7092-63200	7093-63200	5/8	15.9	2	0.969	24.6	24	5.5	200	450
7092-63304	7093-63304	5/8	15.9	4	1.062	27.0	35	5.5	300	450
7092-75200	7093-75200	3/4	19.1	2	1.109	28.2	32	6.0	200	400
7092-75304	7093-75304	3/4	19.1	4	1.156	29.4	37	6.0	300	400
7092-100200	7093-100200	1	25.4	2	1.406	35.7	44	7.0	200	300
7092-100304	7093-100304	1	25.4	4	1.438	36.5	51	8.0	300	300
7092-125204	7093-125204	1-1/4	31.8	4	1.781	45.2	77	9.0	200	250
7092-150204	7093-150204	1-1/2	38.1	4	2.031	51.6	86	10.0	200	200
7092-200154	7093-200154	2	50.8	4	2.550	64.8	113	14.0	200	200

Packaging:	Reels
Crimp Couplings:	Series HY, 43; Refer to CrimpSource at www.safehose.com for coupling recommendations and crimp specifications.



Parker Hannifin Corporation
Industrial Hose Division
Strongsville, OH
www.safehose.com

Parker Industrial Hose Customer Service
866 810 HOSE (4673) 800-242-HOSE (4673)
Strongsville, OH South Gate, CA
Eastern USA Western USA
e-mail indhose@parker.com