



HURRICANE

Pressure Washer Hose

Series 7258

This "Made in the U.S.A." hose offers high pressure (3000 PSI) and temperature (250°F) capability for many industrial pressure washer applications. Hose assemblies are fabricated using Parker manufactured and validated couplings, ensuring safety and quality to the end user. Factory made assemblies are coupled rigid male pipe x male pipe swivel, with strain relievers on each end.

4:1 Design factor

>> Also available in prepackaged coupled assemblies

Tube	Black Neoprene
Cover	Black (BK) or Blue (BL) Neoprene
Reinforcement	One wire braid
Temperature Range	-40° F to +250° F (-40°C to +121°C)
Branding	HURRICANE 3000 7258 XX I.D. 3000 PSI MAX WP MADE IN THE USA (DATE CODE)
Brand Description	Ink Brand - White letter color
Compare to	Gates Power Clean

LENGTHS: 500 ft. reels $\pm 10\%$; 3 pieces max.; lengths in 50 ft. increments.

COUPLINGS: For permanent crimp specifications, refer to CrimpSource. Other available coupling options: Series 43, HY. For assembly guidelines and additional coupling options, refer to NAHAD Industrial Hose Assembly Guidelines.

7258-BK

7258-BL

Applications

- Pressure Washers

Part No.	ID (in.)	ID (mm)	Reinf. Braids	OD (in.)	OD (mm)	Approx. Wt. per 100 Ft.	Min. Bend Radius	Max. Rec. WP
7258-250BK	1/4	6.4	1	0.500	12.7	14	1.5	3000
7258-250BK050	1/4	6.4	1	0.500	12.7	14	1.5	3000
7258-250BL	1/4	6.4	1	0.500	12.7	14	1.5	3000
7258-250BL050	1/4	6.4	1	0.500	12.7	14	1.5	3000
7258-380BK	3/8	9.5	1	0.625	15.7	19	2.0	3000
7258-380BK050	3/8	9.5	1	0.625	15.7	19	2.0	3000
7258-380BL	3/8	9.5	1	0.625	15.7	19	2.0	3000
7258-380BL050	3/8	9.5	1	0.625	15.7	19	2.0	3000
7258-501BK	1/2	12.7	1	0.745	18.9	23	3.0	3000



WARNING! Not recommended for steam service. Not intended for carpet cleaning applications.